

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A radio system comprising:
a portable device that may be carried by a user; and
a stationary device for wirelessly communicating with said portable device, wherein
said portable device operates such that when said portable device receives first signals
from said stationary device, said portable device sends second signals representative of
reception intensity data of the first signals back to said stationary device, and
said stationary device sends the first signals from a plurality of stationary-device side
antennae located at different positions respectively, and when said stationary device receives
the second signals from said portable device through the respective stationary-device side
antennae, said stationary device determines a position of said portable device by using the
reception intensity data of the first signals included in the respective second signals,
wherein said stationary device varies the setting of the amplitude relations between
transmission output powers of the first signals from said respective stationary-device side
antennae and sends the first signals, and said stationary device determines the position of said
portable device by using the reception intensity data obtained for each said setting,
wherein said stationary device determines the position of said portable device as
viewed in a direction in which paired antennae of the stationary-device side antennae are
arrayed by using the magnitude relations between the reception intensity data of the paired
antennae.

2. (Currently Amended) A radio system comprising:
a portable device that may be carried by a user; and
a stationary device for wirelessly communicating with said portable device, wherein
said stationary device sends first signals from a plurality of stationary-device side
antennae located at different positions, and
said portable device operates such that when said portable device receives the first
signals from said stationary-device side antennae of said stationary device, said portable

device determines a position of said portable device by using reception intensity data of the respective first signals, and sends a second signal representative of the result of the position determination back to said stationary device,

wherein said stationary device varies the setting of the amplitude relations between transmission output powers of the first signals from said respective stationary-device side antennae and sends the first signals, and said portable device determines the position of said portable device by using the reception intensity data obtained for each said setting,

wherein said stationary device determines the position of said portable device as viewed in a direction in which paired antennae of the stationary-device side antennae are arrayed by using the magnitude relations between the reception intensity data of the paired antennae.

3. (Currently Amended) A radio system comprising:

a portable device that may be carried by a user and;

a stationary device for wirelessly communicating with said portable device, wherein said portable device sends first signals to said stationary device, and

said stationary device receives the first signals by use of a plurality of stationary-device side antennae located at different positions, and determines a position of said portable device by using reception intensity data of the respective first signals,

wherein said stationary device receives the first signals by varying the setting of the magnitude relations between the reception intensity data of the first signals from the stationary-device side antennae, and determines the position of said portable device by using the reception intensity data obtained for each setting,

wherein said stationary device determines the position of said portable device as viewed in a direction in which paired antennae of the stationary-device side antennae are arrayed by using the magnitude relations between the reception intensity data of the paired antennae.

4 -6. (Canceled).

7. (Original) The radio system according to claim 1, wherein said stationary device is mounted on a vehicle, and said stationary device and/or said portable device judges from the position determination result that said portable device is inside or outside said vehicle, that a user carrying said portable device gets on said vehicle, or that said user gets off said vehicle.

8. (Original) The radio system according to claim 7, wherein said stationary device wirelessly communicates with said portable device to verify that said portable device is a predetermined one, and automatically executes a control process for realizing a predetermined operation of an object to be controlled in said vehicle, and when judging that the user carrying said portable device got on the vehicle, said stationary device selects a kind of the controlled object or control contents of the controlled object.

9. (Original) The radio system according to claim 8, wherein the controlled object includes a device for locking and unlocking the doors of the vehicle, and the control process includes a signal output for causing said device to operate for locking or unlocking.

10. (Original) The radio system according to claim 7, wherein said stationary device wirelessly communicates with said portable device to verify that said portable device is a predetermined one, and automatically executes a control process for realizing a predetermined operation of an object to be controlled in said vehicle, and when judging that the user carrying said portable device got on the vehicle, said stationary device and/or said portable device selects such transmission output power of the wireless communication for the verification as to reduce a communication range.

11. (Original) The radio system according to claim 10, wherein the transmission output power is selected to change the wireless communication range for the verification from a relatively broad remote control range including positions outside the vehicle, which are remote from the vehicle by a predetermined distance, to a narrow range within the vehicle.

12. (New) The radio system according to claim 11, wherein said portable device includes transmission power adjustment means for adjusting the transmission output power in set

increments, and wherein a minimum transmission output power that is received by each of said antennae is selected as the transmission output power for use by said portable device.